

Lifetime Hardware Guarantee

Congratulations!

The product you have purchased includes Blum Concealed Hinges and/or Blum Drawer Runners, the finest in functional hardware. In keeping with our commitment to quality, integrity, and expert workmanship, this hardware meets or exceeds the highest industry standard requirements.

Lifetime guarantee and limited warranty

Blum, Inc. (BLUM) warrants its hinges and/or drawer runners, contained in this product, but not the product itself, against defects in material and workmanship for as long as the original consumer purchaser owns the products. BLUM will send the original consumer purchaser, without charge, a new BLUM hinge or runner to replace any defective BLUM hinge or runner subject to this warranty. This warranty is a warranty of replacement only. BLUM specifically does not warrant removal of the defective hinge or runner nor installation of a new hinge or runner. This warranty does not cover hinges or drawer runners which have been incorrectly installed, exposed to excessive loads or abused.

To obtain a replacement within 30 days of discovery of the defect, remove the defective hinge or runner and mail it postage pre-paid to:

Blum, Inc.
Sample Department
7733 Old Plank Rd.
Stanley, NC 28164

Enclose a letter explaining the defect with a copy of your proof of purchase. Allow approximately four (4) weeks for delivery of the replacement.

ALL WARRANTIES IMPLIED BY STATE LAW, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE EXPRESSLY LIMITED AS SET FORTH ABOVE. However, some states do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you. WITH THE EXCEPTION OF ANY WARRANTIES IMPLIED BY STATE LAW AS HEREBY LIMITED, THE FOREGOING EXPRESS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES OF BLUM WITH RESPECT TO THE REPAIR OR REPLACEMENT OF ANY PROPS OR PARTS. IN NO EVENT SHALL BLUM BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM THE USE, INSTALLATION, PERFORMANCE OR FAILURE OF ITS PRODUCT. However, some states do allow the exclusion of limitation of incidental or consequential damages, so the above exclusion may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.


Blum, Inc.
7733 Old Plank Rd.
Stanley, NC 28164
toll free 800-438-6788
local 704-827-1345
fax 704-827-0799
internet www.blum.us

Perfecting motion 


1085_01_05 © 2005 Printed in USA

Hinge adjustments


COMPACT series
(See inside for adjustments
and installation instructions.)




COMPACT 33 series
Large overlay



COMPACT 33 series
Small overlay



COMPACT 38C/39C series
Large overlay























COMPACT 38N series
Small overlay

Subject to technical modifications without notice © 2005 Blum, Inc.

COMPACT 33 series

COMPACT 38C/39C & 38N series

Side adjustment	Large overlay	Small overlay	Side adjustment	Large overlay	Small overlay
 <p>Loosen front screw, position door, tighten screw. Range = 1/8" (3mm)</p>			 <p>Turn front screw counter-clockwise to increase door overlay, clockwise to decrease. Range = 1/8" (3mm)</p>		
<p>Height adjustment</p>  <p>Loosen screw(s) on the mounting plate. Adjust door to position and tighten screw(s). Range = 9/32" (7mm)</p>			<p>Height adjustment</p>  <p>Loosen center screw. Adjust door to position and tighten screw. Range = 1/4" (6mm)</p>		
<p>Door removal</p> <p>Loosen side adj. screw. Slide hinge off mounting plate towards center of cabinet.</p>			<p>Door removal</p>  <p>Turn back screw counter-clockwise to increase door gap, clockwise to decrease. Range = -1/32" (1mm) + 3/32" (2mm)</p>		
<p>Door installation</p> <p>To reinstall reverse procedure, tighten screws on all hinges.</p>					



Note:
Before finishing hinge installation, place set screw in hinge plate to prevent hinge plate movement.
(1 3/8" or greater overlays only.)